

# Waterlogic 800 Max II

The WL800 Max II is designed to meet the high demands for cold and hot water in high traffic areas. The intuitive paddle operation and tall dispensing area enables users to easily fill large jugs and carafes. With an ultraviolet system to maintain water hygiene and large capacity tanks, you are assured a continuous supply of clean and refreshing water.

Waterlogic's latest high capacity water dispenser for demanding environments.

## Making Water Great

This Waterlogic dispenser offers two great steps to fresh water:



**1. Filtration:** The WL800 uses a four-stage reverse osmosis process to produce the best quality drinking water. It includes a sediment filter, pre carbon filter, reverse osmosis membrane and a post carbon filter. These filters remove impurities and improve taste\* to give you the best water possible.



**2. UV Sanitization:** Re-circulating UV system sanitizes the water by reducing bacterial growth giving a reassurance of fresh clean drinking water.

\* Where applicable



## High quality water in volume

- Cold and hot options
- Easy to clean and use faucets
- Hot water safety feature to protect against accidental usage
- Tall dispensing area is ideal for filling large jugs and carafes
- Re-circulating UV lamp maintains water hygiene
- With RO filtration (reverse osmosis) to make the poorest quality water good
- Sleek profile for good looks and castors on base for easy relocation



## The Boring Bits

Water Options	Technical Features	
	Type available	Tower
	Freestanding dimensions	430mm (W) x 1250mm (H) x 510mm (D) 16.9" (W) x 49.2" (H) x 20.1" (D)
	Dispense area height	298mm (11.7")
	Weight	43.5kg (95lbs)
	Standard filtration supplied	RO (Reverse Osmosis)
	Purification system	UV lamp (4W)
Symbols		
Cold water Hot water	Capacity	Room temperature: 14 liters (3.7 gal) Cold: 16 liters (4.2 gal) Hot: 3.5 liters (1 gal) 500W heater Production rate: 190 L/d (25°C, 138 kPa) (50 gal)
	Additional features	Leak detection Removable drip tray Overfill protection
	Compressor	110V / 60Hz (220v / 50Hz available)
	Water temperatures	Cold: 5°C / 41°F Hot: 85°C / 185°F

## Tested and Certified



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLT Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

## Speak to a Water Expert

